SAFETY DATA SHEET

1. Identification

Product identifier MASON® CS-425

Other means of identification

Product Code 873202 Recommended use Surfactant **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Mason Chemical Company Company name 2744 E. Kemper Rd **Address**

Cincinnati, OH 45241

United States (513) 326-0600 **Telephone**

1-800-707-4568

E-mail sdsinfo@pilotchemical.com

CHEMTREC International: 1-703-527-3887 **Emergency phone number**

CHEMTREC USA: 1-800-424-9300

2. Hazard(s) identification

Category 3 Physical hazards Flammable liquids Health hazards Acute toxicity, oral Category 4 Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment,

long-term hazard

Not classified.

Label elements

OSHA defined hazards



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if swallowed. Causes severe skin burns and eye damage.

Causes serious eye damage. Very toxic to aquatic life. Very toxic to aquatic life with long lasting

Category 1

effects.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly Prevention

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to

extinguish. Collect spillage.

Store in a well-ventilated place. Keep cool. Store locked up. Storage

Material name: MASON® CS-425 SDS US Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Ingestion

Chemical name	Common name and synonyms	CAS number	%
Quaternary Ammonium Compounds.		68424-85-1	50 - < 60
Benzyl-C12-C16-alkyldimethyl, Chlorides			
Ethanol		64-17-5	5 - < 10
Other components below reportable I	evels		40 - < 50

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

blindness could result.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

observation. Symptoms may be delayed.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: MASON® CS-425

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Ai	ir Contaminants (29 CFR 1910.1000)
Components	Type

Ethanol (CAS 64-17-5)	PEL	1900 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Ethanol (CAS 64-17-5)	STEL	1000 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Material name: MASON® CS-425 SDS US

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear. **Appearance** Physical state Liquid. **Form** Liquid.

Color Colorless to Beige.

Odor Almond **Odor threshold** Not available.

7 - 9 рH

Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

116.6 °F (47.0 °C) Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure 44 mm Hg Estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Miscible Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** 68.99 cSt

Other information

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing.

Specific gravity 0.96

VOC 5 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid Conditions to avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Material name: MASON® CS-425 SDS US 873202 Version #: 02 Revision date: 03-12-2019 Issue date: 05-27-2015

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Ethanol (CAS 64-17-5)

<u>Acute</u>

Inhalation Vapor

LC50 Rat 117 - 125 mg/l, 4 h

Oral

LD50 Rat 10470 mg/kg

Causes severe skin burns and eye damage.

Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides (CAS 68424-85-1)

Acute Dermal

LD50 3560

Oral

LD50 430

Skin corrosion/irritation Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Possible reproductive hazard.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Material name: MASON® CS-425

Components **Species Test Results**

Ethanol (CAS 64-17-5)

Aquatic

Acute

EC50 Algae Algae 675 mg/l, 72 h Crustacea EC50 Daphnia 5012 mg/l, 48 h Fish LC50 Fathead minnow (Pimephales promelas) 14200 mg/l, 96 h

Chronic

Crustacea NOEC Daphnia 9.6 ma/l. 9 d

Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides (CAS 68424-85-1)

Aquatic

Acute

LC50 Fish Bluegill (Lepomis macrochirus) 0.515 mg/l

Chronic

NOEL Crustacea Daphnia 0.0042 mg/l

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the **Disposal instructions**

> material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

D001: Waste Flammable material with a flash point <140 F

Dispose in accordance with all applicable regulations.

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN2920

UN proper shipping name Corrosive liquids, flammable, n.o.s. (Quaternary Ammonium Compound, Ethanol)

Transport hazard class(es)

Class 8 Subsidiary risk 3 8, 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B2, IB2, T11, TP2, TP27 Special provisions

Packaging exceptions None Packaging non bulk 202 243 Packaging bulk **ERG** number

Note: Class 3 labels are not required when packages are transported domestically by rail or highway as noted in 49CFR 172.402

(a)

Material name: MASON® CS-425

IATA

UN2920 **UN number**

Corrosive liquid, flammable, n.o.s. (Quaternary Ammonium Compound, Ethanol) **UN proper shipping name**

Transport hazard class(es)

Class 8 Subsidiary risk 3 **Packing group** Ш **Environmental hazards** No. 8F **ERG Code**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

Allowed with restrictions.

aircraft

Other information

Allowed with restrictions. Cargo aircraft only

IMDG

UN2920 **UN number**

UN proper shipping name CORROSIVE LIQUID, FLAMMABLE, N.O.S. (QUATERNARY AMMONIUM COMPOUND,

ETHANOL)

Not established.

Transport hazard class(es)

Class 8 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant No. F-E, S-C **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol (CAS 64-17-5)

Material name: MASON® CS-425 SDS US

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) categories

Skin corrosion or irritation

Serious eye damage or eye irritation

Immediate Hazard - Yes Hazard categories

> Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

Inventory name

California Proposition 65 Pilot Chemical does not provide Proposition 65 information on our safety data sheets. Proposition

65 statements are available upon request by contacting reginfo@pilotchemical.com.

International Inventories

Country(s) or region

Australia Australian Inventory of Chemical Substances (AICS) Yes Yes Canada Domestic Substances List (DSL) Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of Existing Commercial Chemical Yes Substances (EINECS) No Europe European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Yes Japan Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

Material name: MASON® CS-425 SDS US

On inventory (yes/no)*

16. Other information, including date of preparation or last revision

 Issue date
 05-27-2015

 Revision date
 03-12-2019

Version # 02

HMIS® ratings Health: 3

Flammability: 3 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 3 Instability: 0

Disclaimer The Pilot Chemical Corp. product referred to in this document is sold pursuant to Pilot Chemical

Corp.'s Standard Terms and Conditions ("Terms"); however, the information contained in this document shall not be considered part of said Terms. Although the information is believed to be

accurate and reliable as of the date compiled, PILOT CHEMICAL CORP. MAKES NO

GUARANTEE, REPRESENTATION, OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE ACCURACY, RELIABILITY, SUFFICIENCY, SUITABILITY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF ANY INFORMATION IN THIS DOCUMENT OR THE PRODUCT TO WHICH THIS DOCUMENT RELATES. Users should make their own investigations, tests and determinations as to the information's completeness and the product's suitability for their particular purposes. It is the user's responsibility to ensure that all activities comply with applicable laws. Pilot Chemical Corp. makes no warranty or representation that the information or product may be used without infringing the intellectual property rights of Pilot Chemical Corp or others. This document is provided gratuitously for guidance only and Pilot

Chemical Corp. assumes no liability for its use.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: MASON® CS-425 sps us